

BETTER VINTAGE

KCV CENTER PIVOT CONSERVATION ROOF WINDOW



VARIANT	701
PANE	
Construction	4V6-16G1-4H
24 mm double glazing	✓
Low E	✓
Gas	Argon
Toughened	✓
U_g (W/m ² K)	1.1
Total solar energy transmittance	0.6
WINDOW	
U_w (W/m ² K)	1.4
Water tightness	E1350
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	32 [-1,-5] dB
Ventilation valve	✓
COLOUR	
Natural wood	✓



NEXT 20
GUARANTEE



MAX PROTECT



MASTER WOOD



QUICK INSTALL

APPLICABLE

- In public, domestic buildings, for conservation area and for old buildings (for renovation)
- In heated, inhabited rooms
- In roof pitch range of 15-90°
- Suitable on all roofings with proper flashing

FEATURES

- Center pivot
- Black external profiles and black glazing bar
- Extra sliding gasket
- Ventilation valve
- Two passive ventilation positions via handle
- Underfelt foil collar included
- Easy installation
- 10 - 20 year guarantee

MATERIAL / WOOD AND FINISHING

- Kiln-dried laminated pine wood
- Timber from FSC certified forests
- Fungicide protection
- Double layer water-based lacquer

COVER PARTS

- Aluminium, lacquered, RAL 9005

HANDLE

- Ergonomically designed moulded zinc handle, lacquered

HINGE

- Centre pivot



TECHNICAL DATA

MEASURES [cm]

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT	EFFECTIVE LIGHT AREA m ²
KCV C4A	55x98	55	97,8	39,8	84,9	37,3	79	0.295
KCV F6A	66x118	66	117,8	50,8	104,9	48,3	99	0.478
KCV M6A	78x118	78	117,8	62,8	104,9	60,3	99	0.597

FLASHING COMPATIBILITY TABLE

ACCESSORIES COMPATIBILITY TABLE

CODE	FLUSH FLASHING VINTAGE (BLACK)	PLAIN TILE FLASHING VINTAGE (BLACK)	UNIVERSAL FLASHING VINTAGE (BLACK)	BLACKOUT BLIND	ROLLER BLIND	VENETIAN BLIND	ANTI HEAT BLIND	ROLLER SHUTTER
KCV C4A	KFF C4A	KFP C4A	KUF C4A	DUR C4A	RHR CXA	PAR C4A	MIR CXA	SHR C4A
KCV F6A	KFF F6A	KFP F6A	KUF F6A	DUR F6A	RHR FXA	PAR F6A	MIR FXA	SHR F6A
KCV M6A	KFF M6A	KFP M6A	KUF M6A	DUR M6A	RHR MXA	PAR M6A	MIR MXA	SHR M6A

Please check the combi flashing compatibility table as well.

PANE 700
Energy saving insulated glass
4V6-16G1-4H

U_g: 1,1 W/m²K
U_w: 1,4 W/m²K

4mm float glass

Low-E coating [reflects heat]

Argon gas filled cavity

4 mm toughened safety glass

AVAILABLE SIZES [cm]

C4A	F6A	M6A
55x98	66x118	78x118



www.dakea.com