

BETTER VIEW

KHV HIGH PIVOT ROOF WINDOW



VARIANT	1000
PANE	
Construction	33.2V6-14G1-4HV6
24 mm double glazing	✓
Low E	✓✓
Gas	Argon
Toughened	✓
Laminated	✓
U_g (W/m ² K)	1.0
Total solar energy transmittance	0.52
WINDOW	
U_w (W/m ² K)	1.3
Water tightness	E1500
Air permeability	Class 4
Resistance to wind load	Class C4*
Sound reduction	34 [-1,-4] dB
Ventilation valve	✓
COLOUR	
Natural wood	✓

* M8A: no performance data



NEXT 20
GUARANTEE



MAX PROTECT



MASTER WOOD



THERMOSTAT

APPLICABLE

- In public and domestic buildings
- In heated, inhabited rooms
- In roof pitch range of 15-55°
- Suitable on all common roofings with proper flashing

FEATURES

- High pivot
- Gas spring assisted
- Laminated internal pane
- Two passive ventilation positions via handle
- Ventilation valve
- Easy installation
- 10 - 20 year guarantee

MATERIAL / WOOD AND FINISHING

- Kiln-dried laminated pine wood
- Timber from FSC certified forests
- Fungicide protection
- Double layer water-based lacquer

COVER PARTS

- Aluminium, lacquered, RAL 7043

HANDLE

- New, ergonomically designed moulded zinc handle, lacquered

HINGE

- High pivot



TECHNICAL DATA

MEASURES [cm]

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT	EFFECTIVE LIGHT AREA m ²
KHV C4A	55x98	55	97,8	39,8	84,9	37,3	79	0.295
KHV F6A	66x118	66	117,8	50,8	104,9	48,3	99	0.478
KHV M4A	78x98	78	97,8	62,8	84,9	60,3	79	0.476
KHV M6A	78x118	78	117,8	62,8	104,9	60,3	99	0.597
KHV M8A	78x140	78	139,8	62,8	126,9	60,3	121	0.729

FLASHING COMPATIBILITY TABLE

ACCESSORIES COMPATIBILITY TABLE

CODE	SLATE FLASHING	TILE FLASHING	UNIVERSAL FLASHING	BLACKOUT BLIND	ROLLER BLIND	VENETIAN BLIND	ANTI HEAT BLIND	ROLLER SHUTTER
KHV C4A	KSF C4A	KTF C4A	KUF C4A	DUR C4A	RHR CXA	PAR C4A	MIR CXA	SHR C4A
KHV F6A	KSF F6A	KTF F6A	KUF F6A	DUR F6A	RHR FXA	PAR F6A	MIR FXA	SHR F6A
KHV M4A	KSF M4A	KTF M4A	KUF M4A	DUR M4A	RHR MXA	PAR M4A	MIR MXA	SHR M4A
KHV M6A	KSF M6A	KTF M6A	KUF M6A	DUR M6A	RHR MXA	PAR M6A	MIR MXA	SHR M6A
KHV M8A	KSF M8A	KTF M8A	KUF M8A	DUR M8A	RHR MXA	PAR M8A	MIR MXA	SHR M8A

Please check the combi flashing compatibility table as well.

PANE 1000
Energy saving insulated glass
33.2V6-14G1-4HV6

U_g: 1,0 W/m²K
U_w: 1,3 W/m²K

- 3mm float glass
- Two layers of tear resistance foil
- 3 mm float glass
- Low-E coating [reflects heat]
- Argon gas filled cavity
- Low-E coating [reflects heat]
- 4 mm toughened safety glass

AVAILABLE SIZES [cm]

C4A	F6A	M4A	M6A	M8A
55x98	66x118	78x98	78x118	78x140



CE 17
EN 14351-1: 2006
+A1:2010



www.dakea.com