

# ROLLER SHUTTER

## SHR4200E



**10** YEAR  
GUARANTEE

### APPLICABLE

- In public and domestic buildings
- In heated, inhabited rooms
- In roof pitch range of 15-90°
- Suitable on all roofings with proper flashing
- SHR is compatible with all Dakea roof windows\*

\* SHR is not compatible with KFF flashing (recessed installation)

### FEATURES

- The most effective solution against solar heat
- Excludes light
- Protects against burglary
- Gives you 100% privacy
- Improves the U-value up to 0,3 W/m<sup>2</sup>K based on CSTB calculation

### MATERIAL








- Coated aluminium
- Double insulated aluminum slats for increased insulation
- Painted grey, RAL7043

### OPERATION

- Electrical operation
- 24V 4-step tubular motor included radio remote controller
- SHR 4200E can be linked with lo-homecontrol®
- The shutter follows the movement of the sash whether the panzer is up or down
- Reduction of solar heat



### AVAILABLE SIZES [cm]

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |
| <b>C2A</b>  | <b>C4A</b>  | <b>F6A</b>  | <b>M4A</b>  | <b>M6A</b>  | <b>M8A</b>  | <b>S6A</b>  |
| 55x78   | 55x98   | 66x118  | 78x98   | 78x118  | 78x140  | 114x118   |

[www.dakea.com](http://www.dakea.com)

