

# Good™

## KDV Center pivot slim frame roof window



master wood



next 20  
guarantee



max protect

VARIANT	700
<b>Pane</b>	
Construction	4V6-16G1-4H
24 mm double glazing	✓
Low E	✓
Gas (argon)	✓
Toughened	✓
Laminated	-
U <sub>g</sub> (W/m²K)	1.1
Total solar energy transmittance	0.60
<b>Window</b>	
U <sub>w</sub> (W/m²K)	1.5
Water tightness	E1200
Air permeability	Class 4
Resistance to wind load	Class C4*
Sound reduction	32 [-1, -5] dB
<b>Colour</b>	
Natural wood	✓

### Applicable

- In public and domestic buildings
- In heated, inhabited rooms
- In roof pitch range of 15-90°
- Suitable on all roofings with proper flashing

### Features

- Center pivot
- Extra sliding gasket
- Two passive ventilation positions via handle
- Slim frame
- Ventilation valve
- Easy installation
- 10 - 20 year guarantee

### Material | Wood and finishing

- Kiln-dried laminated pine wood
- Timber from FSC certified forests
- Fungicide protection
- Double layer acrylic lacquer

### Cover parts

- Aluminium, lacquered, RAL 7043

### Handle

- Ergonomically designed moulded zinc handle, lacquered

\*sizes up to S6A

### Available sizes [cm]

C2A	C4A	F4A	F6A	M4A	M6A	M8A	M10A	P6A	P8A	S6A	S8A	U4A	U8A
55x78	55x98	66x98	66x118	78x98	78x118	78x140	78x160	94x118	94x140	114x118	114x140	134x98	134x140

# Technical data

## MEASURES [cm]


Code	Nominal Size	Frame External Size		Pane Size		Visible Glass		
		Width	Height	Width	Height	Width	Height	Effective Light Area m <sup>2</sup>
KDV C2A	55x78	55	77,8	39,8	64,9	37,3	59	0.220
KDV C4A	55x98	55	97,8	39,8	84,9	37,3	79	0.295
KDV F4A	66x98	66	97,8	50,8	84,9	48,3	79	0.382
KDV F6A	66x118	66	117,8	50,8	104,9	48,3	99	0.478
KDV M4A	78x98	78	97,8	62,8	84,9	60,3	79	0.476
KDV M6A	78x118	78	117,8	62,8	104,9	60,3	99	0.597
KDV M8A	78x140	78	139,8	62,8	126,9	60,3	121	0.729
KDV M10A	78x160	78	159,8	62,8	146,9	60,3	141	0.850
KDV P6A	94x118	94	117,8	78,8	104,9	76,3	99	0.755
KDV P8A	94x140	94	139,8	78,8	126,9	76,3	121	0.925
KDV S6A	114x118	114	117,8	98,8	104,9	96,3	99	0.953
KDV S8A	114x140	114	139,8	98,8	126,9	96,3	121	1.165
KDV U4A	134x98	134	97,8	118,8	84,9	116,3	79	0.919
KDV U8A	134x140	134	139,8	118,8	126,9	116,3	121	1.407

## FLASHING COMPATIBILITY TABLE

## ACCESSORIES COMPATIBILITY TABLE

Code	Slate Flashing	Tile Flashing	Universal Flashing	Blackout Blind	Roller Blind	Venetian Blind	Anti Heat Blind	Roller Shutter
KDV C2A	KSF C2A	KTF C2A	KUF C2A	DUR C2A	RHR CXA	PAR C2A	MIR CXA	SHR C2A
KDV C4A	KSF C4A	KTF C4A	KUF C4A	DUR C4A	RHR CXA	PAR C4A	MIR CXA	SHR C4A
KDV F4A	KSF F4A	KTF F4A	KUF F4A	DUR F4A	RHR FXA	PAR F4A	MIR FXA	
KDV F6A	KSF F6A	KTF F6A	KUF F6A	DUR F6A	RHR FXA	PAR F6A	MIR FXA	SHR F6A
KDV M4A	KSF M4A	KTF M4A	KUF M4A	DUR M4A	RHR MXA	PAR M4A	MIR MXA	SHR M4A
KDV M6A	KSF M6A	KTF M6A	KUF M6A	DUR M6A	RHR MXA	PAR M6A	MIR MXA	SHR M6A
KDV M8A	KSF M8A	KTF M8A	KUF M8A	DUR M8A	RHR MXA	PAR M8A	MIR MXA	SHR M8A
KDV M10A	KSF M10A	KTF M10A	KUF M10A	DUR M10A	RHR MXA	PAR M10A	MIR MXA	
KDV P6A	KSF P6A	KTF P6A	KUF P6A	DUR P6A	RHR PXA	PAR P6A	MIR PXA	
KDV P8A	KSF P8A	KTF P8A						
KDV S6A	KSF S6A	KTF S6A	KUF S6A	DUR S6A	RHR SXA	PAR S6A	MIR SXA	SHR S6A
KDV S8A	KSF S8A	KTF S8A	KUF S8A	DUR S8A	RHR SXA	PAR S8A	MIR SXA	
KDV U4A	KSF U4A	KTF U4A	KUF U4A	DUR U4A	RHR UXA	PAR U4A	MIR UXA	
KDV U8A	KSF U8A	KTF U8A	KUF U8A	DUR U8A	RHR UXA	PAR U8A	MIR UXA	

Please check the combi flashing compatibility table as well.




### PANE 700

Energy saving insulated glass  
4V6-16G1-4H  
Ug: 1,1 W/m<sup>2</sup>K

- 4 mm float glass
- Low-E coating [reflects heat]
- Stainless steel [warm] edge
- Argon gas filled cavity
- 4 mm toughened safety glass

[www.dakea.com](http://www.dakea.com)



EN 14351-1:2006  
+A1:2010



The mark of responsible forestry